


CLOPAY COMMERCIAL – MODELS 525, 525V, 525S industrial series



Model 525, 10'2" x 16' door

RIBBED STEEL DOORS

Available non-insulated (525) or insulated (525V/525S) with environmentally safe polystyrene insulation conformed to panel. Ideal for commercial and industrial building applications.

- **Polystyrene Insulation**, available on 525V, 525S, provides comfort, energy efficiency and quiet operation in every season.
- **3-Stage Paint Process** delivers a maintenance-free finish.
- **Tog-L-Loc™** construction eliminates welds and rivets for rust-proof and leak-proof joints.
- **Optional Accessories** add functionality while complementing the building.



Panels are pre-painted inside and out to inhibit rust. Hot-dipped, galvanized steel is painted with primer and given a tough oven-baked polyester top coat to provide the most rust-resistant steel door available. Ten-year warranty against rust-through.


clopaycommercial.com

PANEL DESIGN



Deep Ribbed

COLOR OPTIONS



Standard White



Chocolate

Due to the printing process, colors may vary.

CUSTOM PAINT OPTION



Color Blast™ offers more than 1,500 Sherwin-Williams® color options to complement your building design. Clopay's durable factory finish has been thoroughly tested and is backed by a five-year warranty.

FEATURES

STANDARD HARDWARE

18 gauge single-end stiles; 16 gauge double-end stiles

PVC vinyl astragal with aluminum retainer

Commercial 10-ball steel rollers (nylon tires available)

Steel step plate and lift handle

Heavy-duty galvanized end stiles

Inside slide lock for increased security

2" (50.8 mm) or 3" (76.2 mm) track

10,000 cycle springs

Galvanized aircraft cable with minimum 7:1 safety factor

Variety of track configurations to meet building specifications

MATERIALS AND CONSTRUCTION

Panel Thickness 2" (50.8 mm)

Insulation 1-3/8" (34.9 mm) Polystyrene (Available on Models 525V, 525S)

R-value 6.6*

Joining System Tog-L-Loc™

Exterior Steel 25 gauge (.019" min.) (.48 mm)

Interior Cover Vinyl backing (Available on Model 525V)
Painted steel back cover (Available on Model 525S)
30 gauge (.12" min.) (.305 mm)
24 gauge (.023" min.) (.58 mm) optional

Exterior Design Smooth steel, deep ribbed

Max Width 20'2" (6.2 m)

Max Height 18' (5.5 m)

Exterior Colors Standard White and Chocolate. Also available in Color Blast™

Interior Color Standard White

Limited Warranties 10-Year rust-through
1-Year materials and workmanship

*Calculated door section R-value is in accordance with DASMA TDS-163.

For special sizes, applications and options, consult Commercial Information Assistance (CIA) at 1-800-526-4301.



For more information on these and other Clopay products, call 1-800-526-4301 or visit clopaycommercial.com



©2016 Clopay Building Products Company, Inc., a Griffon company.

ADDITIONAL OPTIONS

WINDOW OPTIONS



24" x 6"



24" x 12"



Full View

Glazing options for 525 include DSB glass and plexiglass, tempered glass and wire glass. Prepainted full-view section with standard white or brown finish available with DSB glass and plexiglass, wire glass or insulated glass.

HEAVY-DUTY HARDWARE (where not standard)



Double-end hinge



3" Track



Outside keyed lock

HIGH CYCLE SPRINGS



25,000, 50,000 or 100,000 cycle springs available.

EXHAUST PORT



Can be cut into any type of sectional door. Available in select sizes.



WINDCODE® doors are available in many sizes and pressure ratings.

DISTRIBUTED BY:

